



14V Alternator Controller Units (ACU) Cross Reference

Photo	System	Volt	Engine	Benefits / Features	Approval	Replacement For	Aircraft Eligibility	Zeftronics P/N
	ALT	14V	Single	- Voltage Regulation: 14.2V - Ground-Fault-Protection - Trouble-Shooting Light - Reduced panel light flicker - Low Voltage (Alt off) Warning Light Output - Use R15V00 Rev A for built-in Over-Voltage (OV) Protection	FAA-STC FAA-PMA	Cessna: C611001-0101 Cessna: C611001-0102 Cessna: C611001-0201 Beech: 33-380010 Electrodelta: VR600 Lamar: DGR6 FORD: D4FF-10316-BA, D4FF-10316-CA.	CESSNA: 150, 150A, 150B, 150C, 150D, 150F, 150G, 150H, 150J, 150K, 150L, 150M, A150, A150K, A150L, A150M, F150F, F150G, F150H, F150J, FA150, FA150K, FA150L, FA150M, 172, 172D, 172E, 172F, 172G, 172H, 172I, 172K, 172L, 172M, 172N, 172P, 172Q, F172, F172D, F172E, F172F, F172G, FR172, P172, 177, 177A, 177B, 177RG, F177RG, 180, 180J, 180K, 182, 182M, 182N, 182P, 182Q, F182P, F182Q, T182, 185, A185F, 188, A188B, T188, 206, P206, U206, T206, TU206, 207, 207A, T207, T207A, 210, 210B, 210C, 210D, 210E, 210G, 210H, 210J, 210K, T210, T210G, T210H, T210J, T210K. Beech: 35A33, 35B33, 35C33, E33, E33B, F33, H35, K35, M35, N35, P35. <u>Gulfstream American</u> AA-5, AA-5A, AA-5B.	R15100 Rev A
	ALT	14V	Single	- Voltage Regulation: 14.2V - OV Protection: 16V This is the R15100 Rev A plus built in OV Protection.	FAA-STC FAA-PMA	Cessna: C611001-0101, -0102, -0201. Beech: 33-380010. Lamar: DGR6. Electrodelta: VR600 VR600A FORD: D4FF-10316-BA, -CA.	APPLICABLE FOR ALL AIRCRAFT MODELS LISTED FOR R15100 Rev A.	R15V00 Rev A
	ALT	14V	Single, Twin	- Voltage Regulation: 14.2V - Ground-Fault-Protection - Trouble-Shooting Light - Reduced panel lights flicker - Use R15V0L for built-in OV Protection	FAA-PMA	Piper: 484121, 450392, 6880403, 6880404. Beech: 169-388063. Commander: 1816110. Lamar: B00331-2, B00267-1, 2. Electrodelta: VR200, VR200A. Delco-Remy: 9000590. Wilco: X18150, X17990, X16300B, Prestolite: FVR-4004, FVR-4224, FVR-4011. RBM: 87-87102-21. Lycoming: LW-11357, LW-12747	Piper: PA24-260, 400, PA28-140, 150, 151, 160, 161, 180, 235, 236, PA28S-160, 180. PA28-201T. PA28R-180, 200, 201T. PA28RT-201, 201T. PA32-260, 300, 301, 301T. PA32R-301, 301T. PA32RT-300, 300T. PA32S-300. PA38-112. <u>Grumman American</u> : AA-1B, AA-1C. <u>Rockwell</u> Commander: 112, 112B, 112TC, 112TCA. <u>Bellanca</u> : 7ECA, 7GCAA, 7GCBC, 7KCAB, 8KCAB. Beech: 19, 19A, B19, M19A, A23, A23A, A23-19, B23, C23, A24, A24R, B24R, C24R, S35, V35, V35TC	R1510L
	ALT	14V	Single	- Voltage Regulation: 14.2V - Ground-Fault-Protection, GFP - Trouble-Shooting Light, TSL - Reduced panel lights flicker - OV Protection: 16V - OV & GFP Indicator wire Will work in aircraft approved for the R1510L but user must get field approval before using it	FAA-PMA	Piper: 557-337, Lamar: B00371-1, B00371-14, B00371-8 Electrodelta: VR371 Zeftronics: R1510L (ACU), Plus V1510A (OVR)	Piper: PA24-260, 400, PA28-140, 150, 151, 160, 161, 180, 235, 236, PA28S-160, 180. PA28-201T, PA28R-180, 200, 201, 201T. PA28RT-201, 201T. PA32-260, 300, 301, 301T. PA32R-301, 301T. PA32RT-300, 300T. PA32S-300. PA38-112. <u>Bellanca</u> : 8KCAB, 8GCB. <u>Maule</u> : M-5-180C, 235C. M-6-180, 235. M-7-235, MT-7-235, MX-7-180, 235. MXT-7-160, 180. M-8-235.	R15V0L

14V Alternator Controller Units (ACU) Cross Reference

Photo	System	Volt	Engine	Benefits / Features	Approval	Replacement For	Aircraft Eligibility	Zeftronics P/N
	ALT	14V	Single, Twin	- Voltage Regulation: 14.2V - Externally Adjustable VR - Reduced panel lights flicker - Single or Dual ALT Application - Use R15V0N for built-in Over-Voltage (OV) Protection	FAA-STC FAA-PMA	Prestolite: VSF7201, VSF7202, VSF7202S, VSF7203, VSF7203A, VSF7203S, VSF7204 Electrodelta: VSF7203A TCM: 649684-1 Piper: 550-383	Citabria: 7GCAA, 7ECA, 7GCBC, 7KCAB, 8GCBC. Lake: LA-4, 4A, 4P. Grumman: AA-1, A. Commander: 112, 112B, 112TC, 112TCA. Varga: 2150A Beech: 19A, B19, M19A, 23, 23A, A23A, A23-19, A23-24, B23, C23, C24, A24R, B24R, C24R. Piper: PA23, PA23-160, 235, 250; PA24-260, PA30, PA39; PA60-600, PA60-601, PA60-601P, PA60-602P, PA60-700P. Cessna: 175, 185, 188. Maule: M-5-180C, 3-5-235C; M-6-180, M-6-235; M-7-235; MX-7-180, 235. Schweizer: 269C. Bellanca: 14-19, -19-2, 19-3, 19-3A; 17-30, 17-31, 17-31TC; 17-30A, 17-31A, 17-31ATC. Schweizer: 269C. Gilstream American: AA-1, AA-1A	R1510N
	ALT	14V	Single, Twin	- Voltage Regulation: 14.2V - OV Protection: 16V - Low Voltage warning: 12.7V - Same features as R1510N plus built in OV Protection. - Low/Over-Voltage warning pin	FAA-STC FAA-PMA	Zeftronics: R1510N (ACU), Plus V1510A (OVR)	<i>APPLICABLE FOR ALL AIRCRAFT MODELS LISTED FOR R1510N</i>	R15V0N
	ALT	14V	Single	- Voltage Regulation: 14.2V - OV Protection: 16V - Ground-Fault-Protection (GFP) - OV Protection built-in - GFP & Over-Voltage warning pin - Trouble-Shooting Light	FAA-PMA	Electrodelta: VR415, VR415F. PFT: DGR1-1 Mooney: 800270-505, 880016-503.	Mooney: M20C, M20D, M20E, M20F, M20G, M20J, M20K	R15300
	ALT	14V	Single	- Voltage Regulation: 14.2V - OV Protection: 16V - Ground-Fault-Protection (GFP) - OV Protection built-in - GFP & Over-Voltage warning pin - Trouble-Shooting Light To use in Beech 19, 23, and 24 series as replacement for voltage regulator and OV relay requires mating connector and FAA field approval.	FAA-PMA	Mooney: 880016-501 Electrodelta: VR414. Oeco: 20053, 20065, 20137, 20437, 20082. Lamar: B00403-1. Beech: 35-380093-1, 2, 3. 35-369017-1, 2, 3. Electromech: EM2073-1, 2	Mooney: M20C, M20D, M20E, M20F Beech: H35, J35, K35, M35, N35, P35, S35, V35. V35TC, V35A, V35A-TC, V35B, 36, A36, 33, A33, B33, C33, E33, C33A, E33A, E33C, F33A, F33C.	R1530B