

28V Twin Engine Generator Controller Units (GCU) Cross Reference

Photo	System	Volt	Amp	Generator	Engine	Benefits / Features	Approval	Replacement For	Aircraft Eligibility	Zeftronics P/N
	GEN	24V	25A	Delco Remy Generator	Twin	❖ Voltage Regulation: 28.4V ❖ Current Limit: 25A ❖ Trouble-shooting Light ❖ Reverse Current Protection ❖ G225EN ¹ Requires separate Parallel Relay ❖ G225KN ² Has built-in separate Parallel Relay ❖ Prevents Regulator cycling at low RPM ❖ Eliminates Regulator Noise	FAA-PMA ¹ FAA-PMA ² FAA-STC ²	Delco-Remy: 1118976,B, C, 1118799, 1119218, C, 1118951, 1118975 Electrodelta: VR300-28-25 Cessna: 0850460-8, 4, 6, 7 Beech: 35-380142-13 Lycoming: 71350, 68872 PFT/Lamar: DGR7-28-25	Cessna: 310, 310B, 310C, 310D, 310E, 310F, 310G, 310H, 310I, 310J, 310K, 320, 320A, 320B, 320-1. Beech: 95, B95, B95A, D95A, E95; 95-55, -A55, -B55, -B55A, -C55, -C55A, D55, D55A, E55, E55A. Piper: PA-23-150, PA-23-160, PA-23-235, PA-23-250.	¹ G225EN ² G225KN
	GEN	24V	40A	Delco Remy Generator	Twin	❖ Voltage Regulation: 28.4V ❖ Current Limit: 40A ❖ Trouble-shooting Light ❖ Reverse Current Protection ❖ G240EN ¹ Requires separate Parallel Relay ❖ G240KN ² Has built-in separate Parallel Relay ❖ Prevents Regulator cycling at low RPM ❖ Eliminates Regulator Noise	FAA-PMA ¹ FAA-PMA ² FAA-STC ²	Delco-Remy: 1119237 Electrodelta: VR300-28-40 PFT/Lamar: DGR7-28-40 Beech: 35-380142-15 Lycoming: 71979	Beech: 95, B95, B95A, D95A, E95; 95-55, -A55, -B55, -B55A, -C55, -C55A, D55, D55A, E55, E55A. Commander: 500, 500A, 500B	¹ G240EN ² G240KN
	GEN	24V	50A	Delco Remy Generator	Twin	❖ Voltage Regulation: 28.4V ❖ Current Limit: 50A ❖ Trouble-shooting Light ❖ Reverse Current Protection ❖ G250EN ¹ Requires separate Parallel Relay ❖ G250KN ² Has built-in separate Parallel Relay ❖ Prevents Regulator cycling at low RPM ❖ Eliminates Regulator Noise	FAA-PMA ¹ FAA-PMA ² FAA-STC ²	Delco-Remy: 1119656 Electrodelta: VR300-28-50 PFT/Lamar: DGR7-28-50 Cessna: 0850460-9	Cessna: 310, 310B, 310C, 310D, 310E, 310F, 310G, 310H, 310I, 310J, 310K, 320, 320A, 320B, 320-1. Beech: 95, B95, B95A, D95A, E95; 95-55, -A55, -B55, -B55A, -C55, -C55A, D55, D55A, E55, E55A. Commander: 500, 500A, 500B. Piper: PA-23-150, PA-23-160, PA-23-235, PA-23-250	¹ G250EN ² G250KN
¹ The G225EN, G240EN, G250EN are straight FAA-PMA units requiring only logbook entry when installed. They require an external paralleling (EQ) relay. ² The G225KN, G240KN, G250KN are FAA-STC, FAA-PMA units requiring field approval with the use of FAA form 337 to install. They have built-in paralleling (EQ) relay and require no external EQ relay.										